

#### FORD MOTOR COMPANY

**EXECUTIVE ORDER A-010-1309** 

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

#### IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE		HAUST EMISSION IDARD CATEGORY	USEFL (mi		COM {*=N/A A/E=	RMEDIATE N-USE MPLIANCE or full in-use; exh. / evap. ediate in-use)	FUEL TYPE		
2006	6FMXT04.2PH4	MDV: 3751-5750 Pounds ALVW		SEPA Bin 8a (opt)	EXH / ORVR	EVAP	ЕХН	EVAP	Gasoline (Tier 2		
2000	6FWIX104.2FH4	MDV: 3/31-3/30 FOUNDS ACVVI	Counted as ARB SULEV		120K	150K	*	E	Unleaded)		
No.	o. ECS & SPECIAL FEATURES			EVAPORATIVE FAMILY (EVAF)				DISPLACEMENT (L)			
1	1 2TWC, 2HO2S(2), SFI, EGR, OBD(F)			6FMXR0240NBM							
•	•			6FMXR0240NBN					4.0		
•	*			*				•	4.2		
*	•			•							

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

## **BE IT FURTHER RESOLVED:**

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

## BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

## **BE IT FURTHER RESOLVED:**

That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_ day of July 2005.

Allen Lyons, Chief

Mobile Source Operations Division



New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

# **ATTACHMENT**

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

AVERAGE [g/ml] CH		CH4 R	@ RAF=*	NMOG or NMHC STD	HCHO=for hot-soak;	rmaldehyde; F RL [g/mi]≕run	PM=particul ning loss; (	ale matter; DRVR [g/ga	;RAF=rea alion dispe	clivity ad ensed]=or	justment fac n-board refu	tor; <b>2/3 D</b> [g/ eting vapor r	n monoxide; N test]=2/3 day ecovery; g=gi	diurnal+		
CERT	CERT STD NMO					ml=mile; K=1000 miles; F=degrees Fahrenheil; SFTP=supplemental federal lest procedure  CO [g/mi] NOx [g/mi] HCHO [mg/mi] PM [g/mi] Hwy NOx [g/mi]										
•	•	[g/mi]	[g/mi]	[g/ml]	CERT	[g/mi] STD	CERT	x (g/mi] STE		ERT	STD	CERT	STD	CERT	STD	
ant bes	@ 50K	0,086		0.125	2.3	3.4	0.08	0.14	$\rightarrow$	*	15.	*	*	0.06	0.19	
	@ UL	0.120	•	0.156	3.5	4.2	0.16	0.20	,	•	18.	*	*	0.14	0.27	
	@ 50°F & 4K	*	•	*	*	•	*	*		*	*		*	•	*	
CO [g/mi] @ 20°F & 50K				NMHC+NOx [g/n (composite)				NMHC+NOx [g/ml] [US06]			0 [g/ml] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
				CERT	STD	CERT	STD	CERT	STD	CER	T STD	CERT	STD	CERT	STD	
CERT	7.6	SFTF	@ 50000 miles	0.13	1.02	•	*	*	*	5.4	11.6	*	*	2.9	3.9	
STD	12.5	SFTP	@ 120000 miles	0.25	1.44	*	•	+	*	6.6	16.9	•	*	4.1	5.6	
Evaporative Family			ırnal + Hot s/test) @ U				rnal + Hot Soak i/test) @ UL		Running Loss (grams/mile) @ UL			On-Board Refueling Recovery (grams/galle				
		•	CERT	S	TD CERT		S	STD		CERT		CERT		STD		
	6FMXR0240NBM 0.36			0.	90	0.33	1	.15	0.00	003	0.05		0.07		0.20	
	6FMXR0240NBN 0.36		0,36	0.	90	0.33	i	.15	0,00	103	0.05		0.07		0.20	
	* *		*		*	1		* .	•		+		*		*	
	•		*		*	*		*			•		*		*	

<sup>\* =</sup> not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air- fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel

# 2006 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	INTERMEDIATE IN-USE COMPLIANCE (*=N/A or full in-use; A/E=exh. / evap. Intermediate in-use)		PHASE-IN STD.	OBD II
					EXH	EVAP		
FORD	F-150 PICKUP 2WD	6FMXR0240NBM	1	4.2	*	E	SFTP	Full
FORD	F-150 PICKUP 2WD	6FMXR0240NBN	1	4.2	+	E	SFTP	Full